NOVUS

64-channel IP Recorder

NVR-6364-H8/R





KEY FEATURES

















- •64 x video and audio channels
- •Recording speed up to 1920 fps at 3840 x 2160
- •Supports resolution up to 3840 x 2160
- Recorded stream size: 320 Mb/s in total from all cameras
- •8 x internal place for HDD mounting
- •3 x monitor outputs (HDMI 4K UltraHD, HDMI, VGA)
- •Intelligent image analysis
- •RAID protects recordings

DIMENSIONS



The recorder is dedicated to work with NOVUS 6000 series IP cameras. Detailed data can be found in the compatibility table available in the $\ensuremath{\mathsf{DOWNLOADABLE}}$ FILES tab.

VIDEO

IP Cameras	up to 64 channels at 3840 x 2160 resolution (video + audio)
Maximum Supported Camera Resolution	3840 x 2160
Compression	H.264, H.265, H.265+, H.265 Smart
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 x VGA \bullet spot: 1 x HDMI (FullHD)
Dualstreaming Support	yes
Fisheye Support	yes, 6000 IP series cameras $ullet$ using NVR, any web browser, N-VID6, N Control 6000
AUDIO	
Audio Input/Output	1 x line-in (RCA) / 1 x HDMI, 1 x line-out (RCA)
RECORDING	
Stream Size	320 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, alarm input, motion detection, intelligent image analysis functions
Prealarm/Postalarm	up to 5 s/up to 600 s
DISPLAY	
Display Speed	1920 fps (64 x 30 fps)
PLAYBACK	
Playback Speed	480 fps (16 x 30 fps)
Recorded Data Search	by date/time, events, image analysis events, POS, motion in a defined area, tags, license plate number
BACKUP	
Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	MP4, AVI, RPAS (player included)
STORAGE	
Internal Storage	available mount: 8 x HDD 3.5" 14 TB SATA
Total Internal Capacity	112 TB
RAID Mode	RAID0, RAID1, RAID5, RAID6, RAID10
ALARM	
Internal Alarm Input/Output	8/4 relay type





64-channel IP Recorder NVR-6364-H8/R

Supports camera's motion detection	Camera Alarm Input/Output	supports IP camera's alarm input/output
INTELLIGENT IMAGE ANALYSIS Supported Functions Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance, Face Detection, Perimeter intrusion Detection by pedestrian or vehicle, Line Cross Detection by pedestrian or vehicle, Analysis of Recognized Number Plate Numbers (LPR) Database Capacity 1000 license plates NETWORK Network Interface 2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s Network Protocols Support HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPNP, SMMP, IEEE 802.1X, PPP0E, SMTP, P2P, POS, HTML5 PC/MAC Software NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 Robbile applications Number of Simultaneous Connectionsup to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Motion Detection	supports camera's motion detection
Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance, Face Detection, Perimeter Intrusion Detection by pedestrian or vehicle, Line Cross Detection by pedestrian or vehicle, Analysis of Recognized Number Plate Numbers (LPR) Database Capacity 1000 license plates NETWORK Network Interface 2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s Network Protocols Support UPTP, IPV4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPRP, SNMP, IEEE 802.1X, PPPoE, SMTP, P2P, POS, HTML5 PC/MAC Software NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 Mobile applications N-VID6 (iPhone, Android) Number of Simultaneous Connectionsup to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature - 10°C ~ 50°C	System Reaction to Alarm Events	
Zone entrance, Abandoned Object, Object Disappearance, Face Detection, Perimeter Intrusion Detection by pedestrian or vehicle, Line Cross Detection by pedestrian or vehicle, Analysis of Recognized Number Plate Numbers (LPR) Database Capacity 1000 license plates NETWORK Network Interface 2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s Network Protocols Support HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPNP, SMMP, IEEE 802.1X, PPPOE, SMTP, P2P, POS, HTML5 PC/MAC Software NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 Mobile applications N-VID6 (iPhone, Android) Number of Simultaneous Connectionapu to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network system Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature - 10°C ~ 50°C	INTELLIGENT IMAGE ANALYSI	s
NETWORK Network Interface 2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s Network Protocols Support HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPPP, SNMP, IEEE 802.1X, PPPoE, SMTP, P2P, POS, HTML5 PC/MAC Software NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 Mobile applications N-VID6 (iPhone, Android) Number of Simultaneous Connectionsup to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Supported Functions	Zone entrance, Abandoned Object, Object Disappearance, Face Detection, Perimeter Intrusion Detection by pedestrian or vehicle, Line Cross Detection by pedestrian or vehicle, Analysis of Recognized
Network Interface 2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s Network Protocols Support HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, IEEE 802.1X, PPPoE, SMTP, P2P, POS, HTML5 PC/MAC Software NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 Mobile applications N-VID6 (iPhone, Android) Number of Simultaneous Connectionsup to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES 2 x USB 2.0, 1 x USB 3.0, USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Uinux OSD Usanguages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Con	Database Capacity	1000 license plates
Network Protocols Support HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, IEEE 802.1X, PPPoE, SMTP, P2P, POS, HTML5 PC/MAC Software NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 Mobile applications N-VID6 (iPhone, Android) Number of Simultaneous Connectionsup to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	NETWORK	
UPnP, SNMP, IEEE 802.1X, PPPOE, SMTP, P2P, POS, HTML5 PC/MAC Software NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 Mobile applications N-VID6 (iPhone, Android) Number of Simultaneous Connectionsup to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Network Interface	2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s
AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000, Edge/Safari, N Control 6000 Mobile applications N-VID6 (iPhone, Android) Number of Simultaneous Connectionsup to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Network Protocols Support	
Number of Simultaneous Connectionsup to 128 clients, up to 68 main streams or 256 substreams or 32 playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	PC/MAC Software	AC, NMS, Internet Explorer, Firefox, Chrome, Opera, N Control 6000,
playback streams in total Bandwidth 320 Mb/s in total to all client workstations PTZ PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Mobile applications	N-VID6 (iPhone, Android)
PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Number of Simultaneous Connection	
PTZ Functions pan/tilt/zoom, preset commands AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Bandwidth	320 Mb/s in total to all client workstations
AUXILIARY INTERFACES USB Ports 2 x USB 2.0, 1 x USB 3.0, OPERATING SYSTEM Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	PTZ	
OPERATING SYSTEM Operating System Linux OSD Ianguages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	PTZ Functions	pan/tilt/zoom, preset commands
OPERATING SYSTEM Operating System Linux OSD Ianguages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	AUXILIARY INTERFACES	
Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C		2 x USB 2.0, 1 x USB 3.0,
Operating System Linux OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	ODEDATING SYSTEM	
OSD languages: Polish, English, others Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C		Lieuw
Control PC mouse and IR remote controller (in-set included), network System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C		·
System Diagnostic automatic control of: HDDs, network, camera connection loss Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C		
Security password protection, IP filtering, MAC filtering, ARP guard INSTALLATION PARAMETERS Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Control	PC mouse and IR remote controller (in-set included), network
Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	, ,	automatic control of: HDDs, network, camera connection loss
Dimensions (mm) 430 (W) x 90 (H) x 453 (D) Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Security	password protection, IP filtering, MAC filtering, ARP guard
Weight 6 kg (without HDD) Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	INSTALLATION PARAMETERS	
Power Supply 100 ~ 240 VAC Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Dimensions (mm)	430 (W) x 90 (H) x 453 (D)
Power Consumption 175 W (with 8 HDDs) Operating Temperature -10°C ~ 50°C	Weight	6 kg (without HDD)
Operating Temperature -10°C ~ 50°C	Power Supply	100 ~ 240 VAC
	Power Consumption	175 W (with 8 HDDs)
	Operating Temperature	-10°C ~ 50°C
	· · · · · · · · · · · · · · · · · · ·	2U

The availability of individual functions (including image analysis) depends on the model of the cameras used, as well as the software version of the recorder and cameras.

Presented display and playback speeds are achieved using dual-streaming. Detailed data on hard drives can be found in the compatibility table available in the DOWNLOADABLE FILES tab.



