

NMS IP Recorder



PRO SERIES

KEY FEATURES

H	265			
NDD	250 mb/s Stream	3300 fps ● REC	* x110 V+A	Monitor

•Video and audio channels: 200

•Supports resolution up to 4000 x 3000 •Recorded stream size: 450 Mb/s in total from all


cameras • Supports up to 3 monitors simultaneously

•Built-in HDDs: 12 x 12 TB server-dedicated SAS for 24/7 recording

•RAID controller protects recordings •External arrays support

•Operating system: Microsoft Windows 10 IoT •Compatible with all NOVUS IP cameras •Redundant PSUs: 2

DIMENSIONS



IP Camera Recording	160 channels at 1920x1080 (video+audio) using H.264 codec • 200 channels at 1920x1080 (video+audio) using H.265 codec
Maximum Supported Camera Resolution	4000x3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Cameras and Protocols	Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye
Dualstreaming Support	yes
DISPLAY	
Monitor Output	3 x Mini Display Port 1.2, (up to 3 monitors simultaneously)
Maximum Resolution	3 x 4K UltraHD
AUDIO	
Audio input	1 x Mic in(3,5mm)
Audio Output	3 x Mini Display Port 1.2
Audio Input/Output in Cameras	Supports audio input/output build in cameras
PERFORMANCE - H.264	
2MPX IP Camera	Recording up to: 160 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 160 main streams) • Playback up to: 8 main streams (while recording: 160 main streams)
4MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 120 main streams) • Playback up to: 8 main streams (while recording: 120 main streams)
5MPX IP Camera	Recording up to: 100 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 100 main streams) • Playback up to: 8 main streams (while recording: 8 main streams)
8MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 6 main streams (while recording: 80 main streams) • Playback up to: 6 main streams (while recording: 80 main streams)
12MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 4 main streams (while recording: 80 main streams) • Playback up to: 4 main streams (while recording: 80 main streams)
PERFORMANCE - H.265	
2MPX IP Camera	Recording up to: 200 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 200 main streams) • Playback up to: 8 main streams (while recording: 200 main streams)





NMS IP Recorder NMS NVR X-2U/144

4MPX IP Camera	Recording up to: 160 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 8 main streams (while recording: 160 main streams) • Playback up to: 8 main streams (while recording: 160 main streams)	
5MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 8 sub streams or 4 main streams (while recording: 120 main streams) • Playback up to: 4 main streams (while recording: 120 main streams)	
8MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) Display up to: 8 sub streams or 4 main streams (while recording: 90 main streams) • Playback up to: 4 main streams (while recording: 90 main streams)	
12MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) Display up to: 8 sub streams or 4 main streams (while recording: 90 main streams) • Playback up to: 4 main streams (while recording: 90 main streams)	
RECORDING		
Recording Mode	Continuous, Schedule, Panic, Triggered: manually, by alaram input, motion detection, video analysis, POS, temerature alarm	
Schedule	individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes	
Prealarm/Postalarm	Up to: 30s / Up to: 600s	
PLAYBACK		
Recorded Data Search	By Date/Time, Events, "Text-in", Image Analysis Events	
BACKUP		
Backup Methods	USB port (HDD lor Flash drive), Network	
Backup File Format	JPEG, BMP, AVI, NMS	
HDD		
Internal storage for system	1 x HDD 2.5" SATA	
Internal Storage for Recording	12 x 12TB HDD 3,5" surviliance grade server storage media	
RAID Redundancy	RAID types: RAID 0, RAID 1, RAID 5, RAID 6	
ALARMS		
Alarm Input/output in cameras	support of alarm input and output built in cameras	
Motion detection	support of motion detection built in cameras	
Video Analytics	supported built in analytics in camera	
Temperature alarm	support of temperature alarm built in cameras	
Licence plate recognition (LPR)	support of selected image analysis functions available in the camera	
NETWORK		
Network Interface	2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s	
Network Throughput	up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card	
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, Multicast, FTP, DHCP, DNS, DDNS NTP, RTSP, SAMBA	
Compatible Mobile Applications	NMS Mobile	
PTZ		
PTZ Functions	pan, tilt, zoom, preset commands, patterns, tours, auto-scans, focus, iris	





NMS IP Recorder NMS NVR X-2U/144

ADDITIONAL INTERFACES

USB Ports	6 x USB 3.0,
OPERATING SYSTEM	
Operating System	Microsoft Windows 10 IoT
Recording and Surveillance System	NMS (Novus Management System)
Additional Software	NMS, Internet Explorer
Operation Mode	Pentaplex
OSD	Polish, English, Russian, others
Control	PC mouse and keyboard (in-set included), DCZ keyboard
System Diagnostic	automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss
Security	Password protection, IP filtering, MAC filtering, Limiting the number of connections
INTEGRATION	

Integrated Devices

Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, NMS-ANPR Software, DSC Systems, POS Systems (Posnet, Upos and other), ONVIF Devices, RTSP Devices

INSTALLATION PARAMETERS

Dimensions (mm)	437 (W) x 89 (H) x 648 (D)
Weight	24 kg (with HDDs)
Power Supply	built in 2 x redundant power supply 230VAC input with 960W power each
Power consumption/heatprint	490W/400W (without HDD for recording)
Operating Temperature	5°C ~ 35°C
RACK Mount 19"	20

Attention: To support more than 1 RTSP stream and 1 ONVIF stream you will need special licence key. From serial number: WA 3617 4395, devices have Microsoft Windows 10 IoT operating system.

