NOVUS

IP Recorder

NVR-4416P16-H2/F





KEY FEATURES






















- •16 x PoE Ethernet ports
- •16 x video and audio channels
- •Recording speed up to 480 fps at 3840 x 2160
- Recorded stream size: 168 Mb/s in total from all cameras
- •2 x internal place for HDD mounting
- •2 x monitor outputs (HDMI 4K UltraHD, VGA)
- •Face recognition

DIMENSIONS





VIDEO

IP Cameras	up to 16 channels at 3840 x 2160 resolution (video + audio)
Maximum Supported Camera Resolution	3840 x 2160 • 3000 x 3000 for fisheye cameras
Compression	H.264, H.265
Monitor Output	main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 x VGA (up to 2 monitors simultaneously)
Dualstreaming Support	yes
Fisheye Support	yes, 2000/4000 IP series cameras
AUDIO	
Audio Input/Output	1 x line-in (RCA) / 1 x HDMI, 1 x line-out (RCA)
RECORDING	
Recording Speed	480 fps (16 x 30 fps for 3840 x 2160 and lower)
Stream Size	168 Mb/s in total from all cameras
Recording Mode	continuous, triggered by: manual, alarm input, motion detection, face recognition, intelligent image analysis functions, PIR alarm
Prealarm/Postalarm	up to 3 s/up to 600 s
DISPLAY	
Display Speed	480 fps (16 x 30 fps)
PLAYBACK	
Playback Speed	240 fps (8 x 30 fps)
Recorded Data Search	by date/time, events, image analysis events, motion in a defined area, related to face recognition, tags
BACKUP	
Backup Methods	USB port (HDD or Flash memory), network
Backup File Format	JPG, BMP, PNG, MP4, AVI, RF
STORAGE	
Internal Storage	available mount: 2 x HDD 3.5" 14 TB SATA
Total Internal Capacity	28 TB
ALARM	
Camera Alarm Input/Output	supports IP camera's alarm input/output
System Reaction to Alarm Events	buzzer, e-mail, screen message, recording activation, PTZ, Full Screen, FTP picture upload, FTP video upload, picture to Cloud, video to Cloud
INITELLIGENT INACE ANALYS	10







IP Recorder NVR-4416P16-H2/F

Supported Functions	Exception, Tripwire, Zone entrance, Abandoned Object, Object Disappearance, Face Detection, Pedestrian Detection, Cross Counting, Face Recognition, Sound detection
NETWORK	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s • 16 x Ethernet PoE (IEEE802.3af, Class 3) - RJ-45 interface, 10/100 Mbit/s, with Extended mode
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, SMTP, P2P
PC/MAC Software	NMS, Internet Explorer, NHDR-5000 Viewer/NHDR-5000 Viewer
Mobile applications	RxCamView (iPhone, Android)
Number of Simultaneous Conn	ectionsup to 40 clients
Bandwidth	168 Mb/s in total to all client workstations
PTZ	
PTZ Functions	pan/tilt/zoom, preset commands, patterns
AUXILIARY INTERFACES	
USB Ports	1 x USB 3.0, 2 x USB 2.0,
OPERATING SYSTEM	
0	
Operating System	Linux
OSD Operating System	Linux languages: Polish, English, others
OSD	languages: Polish, English, others
OSD Control	languages: Polish, English, others PC mouse and IR remote controller (in-set included), network
OSD Control System Diagnostic	languages: Polish, English, others PC mouse and IR remote controller (in-set included), network automatic control of: HDDs, network, camera connection loss password protection, IP filtering
OSD Control System Diagnostic Security	languages: Polish, English, others PC mouse and IR remote controller (in-set included), network automatic control of: HDDs, network, camera connection loss password protection, IP filtering
OSD Control System Diagnostic Security INSTALLATION PARAMET	languages: Polish, English, others PC mouse and IR remote controller (in-set included), network automatic control of: HDDs, network, camera connection loss password protection, IP filtering
OSD Control System Diagnostic Security INSTALLATION PARAMET Dimensions (mm)	languages: Polish, English, others PC mouse and IR remote controller (in-set included), network automatic control of: HDDs, network, camera connection loss password protection, IP filtering ERS 300 (W) x 53 (H) x 297 (D)
OSD Control System Diagnostic Security INSTALLATION PARAMET Dimensions (mm) Weight	languages: Polish, English, others PC mouse and IR remote controller (in-set included), network automatic control of: HDDs, network, camera connection loss password protection, IP filtering ERS 300 (W) x 53 (H) x 297 (D) 1.5 kg (without HDD)

Intelligent image analysis, dualstream mode, PTZ control, motion detection and alarm inputs / outputs functions depends on the functionality of the camera and the capabilities of the communication protocol. The recorder is dedicated to work with Novus 2000 and 4000 series IP cameras and achieves the best functionality with them. Detailed data on camera compatibility with recorders and compatible hard drives can be found in the compatibility tables available in the DOWNLOADABLE FILES tab. Display and playback speeds are achieved using dual stream.

One of the functions: Fisheye Support, Face Recognition can be switched on at the same time.



