NoVus

NVSO Client Station NVSO CLIENT 5-4U-II



KEY FEATURES







- •Monitoring of up to 42 channels
- •Supports resolution up to 4000 x 3000
- •Supports up to 3 monitors simultaneously
- •Operating system: Microsoft Windows 10 Pro
- •Compatible with all NMS Network Video Recorders
- Integration with:recorders AHD NOVUS, systems of SSWiN DSC, systems of NMS ANPR, systems POS (Posnet, Upos i inne)

DIMENSIONS



VIDEO

IP Cameras	up to 50 channels at 640 x 480 resolution resolution using H.264 codec (video + audio) • up to 30 channels at 640 x 480 resolution resolution using H.265 codec (video + audio)
Maximum Supported Camera Resolution	4000 x 3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Protocols	Novus, ONVIF, RTSP
Dualstreaming Support	yes
DISPLAY	
Monitor Output	1 x HDMI 2.0b, 1 x Display Port 1.2, 1 x Dual link-DVI, (up to 3 monitors simultaneously)
Maximum Resolution	3 x 4K UltraHD
AUDIO	
Audio input	1 x Line in (3,5mm), 1 x Mic in(3,5mm)
Audio Output	1 x Line output (3,5mm), 1 x HDMI, 1 x Display Port
PERFORMANCE - H.264	
2MPX IP Camera	Display up to: 50 sub streams or 12 main streams • Playback up to: 12 main streams
4MPX IP Camera	Display up to: 45 sub streams or 8 main streams • Playback up to: 8 main streams
5MPX IP Camera	Display up to: 45 sub streams or 6 main streams • Playback up to: 6 main streams
8MPX IP Camera	Display up to: 40 sub streams or 4 main streams • Playback up to: 4 main streams
12MPX IP Camera	Display up to: 35 sub streams or 4 main streams • Playback up to: 4 main streams
PERFORMANCE - H.265	
2MPX IP Camera	Display up to: 30 sub streams or 8 main streams • Playback up to: 8 main streams
4MPX IP Camera	Display up to: 30 sub streams or 4 main streams • Playback up to: 4 main streams
5MPX IP Camera	Display up to: 35 sub streams or 4 main streams • Playback up to: 4 main streams
8MPX IP Camera	Display up to: 35 sub streams or 2 main streams • Playback up to: 2 main streams
12MPX IP Camera	Display up to: 20 sub streams or 2 main streams • Playback up to: 2
	main streams





NVSO Client Station NVSO CLIENT 5-4U-II

Recorded Data Search	by date/time, events, "Text-in"
BACKUP	
Backup Methods	USB port (HDD or Flash memory), network
STORAGE	
Internal storage for system	built-in: 1 x HDD 3,5" SATA
NETWORK	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s
Bandwidth	350 Mb/s in total from all NVRs
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, RTSP, UPnP, SNMP
Mobile applications	NMS Mobile
PTZ	
PTZ Functions	pan/tilt/zoom, preset commands, patterns, tours, auto-scans
AUXILIARY INTERFACES	
USB Ports	6 x USB 3.0,
OPERATING SYSTEM	
Operating System	Microsoft Windows 10 Pro
Operation Mode	triplex
OSD	languages: Polish, English, Russian, others
Control	PC mouse and keyboard (in-set included)
System Diagnostic	automatic control of: HDDs, temperature, fan, network
Security	password protection, IP filtering, MAC filtering, limiting the number of connections
INSTALLATION PARAMETERS	
Dimensions (mm)	427 (W) x 177 (H) x 450 (D)
RACK Mount 19"	4U
Weight	20 kg
Power Supply/Power Consumption	built-in PSU 230 VAC/700 W
Power consumption/heatprint	260W/210W (without HDD for recording)
Operating Temperature	5°C ~ 35°C

Attention.

From serial number: XX 2417 4170, devices have Microsoft Windows 10 Pro operating system. Performance specifications described in the above are valid from serial WA 2519 5776



