

### Speed Dome IP Camera with face recognition and intelligent object tracking

#### NVIP-2SD-6540/25/F





#### **KEY FEATURES**























- •Resolution: 2 MPX
- •Lens: motorized varifocal, Al and AF function, optical zoom 25x, f=4.8  $\sim$  120 mm/F1.65  $\sim$  3.8
- •D/N function IR cut filter
- •Auto Tracking
- •Video content analysis based on Deep Learning
- •microSD card support
- •WDR with double scan sensor
- •Min. Illumination from 0.001 lx (0 lx, IR on)
- $\bullet$  IR LED, range up to 150 m (depends on current optical zoom value)

#### **DIMENSIONS**

The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the  $\ensuremath{\mathsf{DOWNLOADABLE}}$  FILES tab.

IMAGE	
Image Sensor	2 MPX CMOS sensor 1/2.8" SONY
Number of Effective Pixels	1920 (H) x 1080 (V)
Min. Illumination	0.005 lx/F1.65 - color mode • 0.001 lx/F1.65 - B/W mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto: 1 s ~ 1/100000 s
Digital Slow Shutter (DSS)	up to 1 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
LENS	
Optical Zoom	25x
Lens Type	motorized, auto-iris function, f=4.8 $\sim$ 120 mm/F1.65 $\sim$ F3.8
Auto-focus	zoom trigger, day/night mode trigger, manual trigger

## **DAY/NIGHT**

Switching Type	mechanical IR cut filter	
Switching Mode	auto, manual, time	
Switching Level Adjustment	yes	
Switching Schedule	yes	
Visible Light Sensor	yes	

#### **NETWORK**

Stream Resolution	$1920 \times 1080$ (Full HD), $1280 \times 720$ (HD), $704 \times 576$ , $704 \times 480$ , $640 \times 480$ (VGA), $352 \times 288$ (CIF), $352 \times 240$
Frame Rate	30 fps for each resolution
Multistreaming Mode	3 streams
Video/Audio Compression	H.264, H.265, MJPEG/-
Number of Simultaneous Connec	ctionsmax. 6
Bandwidth	50 Mb/s in total






## NoVus

173 mm



300 mm



82 mm

115 mm

## Speed Dome IP Camera with face recognition and intelligent object tracking

NVIP-2SD-6540/25/F

Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, ICMP
Camera Configuration	from Internet Explorer browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	SuperLive Plus (iPhone, Android)
PTZ	
Preset Commands	360 including 20 special (function) presets
Tours	8 (up to 16 presets per tour)
Patterns	4 (max. 360 commands or 180 s for each pattern)
Tilt/Pan Range	-3° ~ 90°/360° (continuous)
Pan/Tilt Speed	up to 80°/s (proportional to zoom)
Preset Speed	up to 80°/s
OTHER FUNCTIONS	
Privacy Zones	4
Motion Detection	yes
Video Content Analysis (VCA)	auto tracking linked to Video Content Analysis (VCA) functions, tamper, line cross, zone entrance, zone exit, cross counting, scene change, video blurred, video color cast, zone entrance detection and object tracking, objects distinguishing, face recognition
Image Processing	180° image rotation, sharpening, mirror effect
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, object tracking
Restoring default settings	via web browser, via NMS IPTool software
IR LED	
LED Number	6
Range	up to 150 m (depends on current optical zoom value)
Smart IR	yes (hardware support)
INTERFACES	
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
INSTALLATION PARAMETERS	
Dimensions (mm)	173 (Φ) x 268 (H) with bracket: 173 (W) x 415 (H) x 300 (L)
Weight	2.1 kg with bracket: 2.8 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, IK10 impact rating, in set: outdoor housing (integrated with the camera), wall mount bracket
Power Supply	12 VDC, PoE+ (IEEE 802.3at, Class 4)
Power Supply Surge protection	12 VDC, PoE+ (IEEE 802.3at, Class 4)  TVS 4000 V
Surge protection	TVS 4000 V





# Speed Dome IP Camera with face recognition and intelligent object tracking NVIP-2SD-6540/25/F

Humidity	max. 90%, relative (non-condensing)
Built-in Heater/Fan	yes/yes

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name).

