

NMS IP Recorder



KEY FEATURES



•Video and audio channels: 140 •Recording speed up to 3500 fps at 1920 x 1080 •Supports resolution up to 4000 x 3000 •Recorded stream size: 350 Mb/s in total from all cameras •Supports up to 3 monitors simultaneously •optional disk mounting: 6 x SATA 3,5"

•Operating system: Microsoft Windows 10 IoT •Recording and surveillance system: NMS (Novus Management System)

•Compatible with all NOVUS IP cameras

DIMENSIONS



* 4 160 mm 428 mm

VIDEO

VIDEO	
IP Camera Recording	100 channels at 1920x1080 (video+audio) using H.264 codec • 140 channels at 1920x1080 (video+audio) using H.265 codec
Maximum Supported Camera Resolution	4000x3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Cameras and Protocols	Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye
Dualstreaming Support	yes
DISPLAY	
Monitor Output	1 x HDMI 2.0b, 1 x Display Port 1.4, 1 x Dual link DVI-D (up to 3 monitors simultaneously)
Maximum Resolution	3 x 4K UltraHD
AUDIO	
Audio input	1 x Line in (3,5mm), 1 x Mic in(3,5mm)
Audio Output	1 x Line (3,5mm), 1 x HDMI, 1 x Display Port
Audio Input/Output in Cameras	Supports audio input/output build in cameras
PERFORMANCE - H.264	
2MPX IP Camera	Recording up to: 100 main streams (while displaying: 8 sub streams) • Display up to: 42 sub streams or 13 main streams (while recording: 42 main streams) • Playback up to: 13 main streams (while recording: 42 main streams)
4MPX IP Camera	Recording up to: 65 main streams (while displaying: 8 sub streams) • Display up to: 40 sub streams or 7 main streams (while recording: 40 main streams) • Playback up to: 7 main streams (while recording: 40 main streams)
5MPX IP Camera	Recording up to: 60 main streams (while displaying: 8 sub streams) • Display up to: 35 sub streams or 5 main streams (while recording: 35 main streams) • Playback up to: 5 main streams (while recording: 35 main streams)
8MPX IP Camera	Recording up to: 36 main streams (while displaying: 8 sub streams) • Display up to: 32 sub streams or 3 main streams (while recording: 32 main streams) • Playback up to: 3 main streams (while recording: 32 main streams)
12MPX IP Camera	Recording up to: 32 main streams (while displaying: 8 sub streams) • Display up to: 26 sub streams or 3 main streams (while recording: 26 main streams) • Playback up to: 3 main streams (while recording: 26 main streams)
PERFORMANCE - H.265	
2MPX IP Camera	Recording up to: 140 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 6 main streams (while recording: 30 main streams) • Playback up to: 6 main streams (while recording: 30 main streams)



NMS IP Recorder NMS NVR 3-T-III

4MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 3 main streams (while recording: 30 main streams) • Playback up to: 3 main streams (while recording: 30 main streams)
5MPX IP Camera	Recording up to: 70 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 3 main streams (while recording: 30 main streams) • Playback up to: 3 main streams (while recording: 30 main streams)
8MPX IP Camera	Recording up to: 60 main streams (while displaying: 8 sub streams) • Display up to: 28 sub streams or 2 main streams (while recording: 28 main streams) • Playback up to: 2 main streams (while recording: 28 main streams)
12MPX IP Camera	Recording up to: 48 main streams (while displaying: 8 sub streams) • Display up to: 20 sub streams or 2 main streams (while recording: 20 main streams) • Playback up to: 2 main streams (while recording: 20 main streams)
RECORDING	
Recording Mode	Continuous, Schedule, Panic, Triggered: manually, by alaram input, motion detection, video analysis, POS, temerature alarm
Schedule	individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes
Prealarm/Postalarm	Up to: 30s / Up to: 600s
PLAYBACK	
Recorded Data Search	By Date/Time, Events, "Text-in"
BACKUP	
Backup Methods	USB port (HDD lor Flash drive), Network
Backup File Format	JPEG, BMP, AVI, NMS
HDD	
Internal storage for system	1 x SSD NVMe
Internal Storage for Recording	6 available bays for 3,5" HDD surveillance grade storage media
ALARMS	
Alarm Input/output in cameras	support of alarm input and output built in cameras
Motion detection	support of motion detection built in cameras
Video Analytics	supported built in analytics in camera
Temperature alarm	support of temperature alarm built in cameras
Licence plate recognition (LPR)	support of selected image analysis functions available in the camera
System Reactions to Alarm Events	e-mail, Screen Message, Recording Activation, PTZ
NETWORK	
Network Interface	1 x Ethernet - RJ45 interface, 10/100/1000/2500 Mbit/s
Network Throughput	up to 350Mbit/s from all cameras • up to 350Mbit/s to all client stations • Max network throughput: 350Mbit/s for each network card
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, SAMBA
Compatible Mobile Applications	NMS Mobile
PTZ	
PTZ Functions	pan, tilt, zoom, preset commands, patterns, tours, auto-scans, focus, iris





NMS IP Recorder NMS NVR 3-T-III

ADDITIONAL INTERFACES

USB Ports	4 x USB 3.2,	
OPERATING SYSTEM		
Operating System	Microsoft Windows 10 IoT	
Recording and Surveillance System	NMS (Novus Management System)	
Additional Software	Internet Explorer	
Operation Mode	Pentaplex	
OSD	Polish, English, Russian, others	
Control	PC mouse and keyboard (in-set included), DCZ keyboard	
System Diagnostic	automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss	
Security	Password protection, IP filtering, MAC filtering, Limiting the number of connections	
INTEGRATION		
Integrated Devices	Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, NMS-	

ANPR Software, DSC Systems, POS Systems (Posnet, Upos and other), ONVIF Devices, RTSP Devices

INSTALLATION PARAMETERS

Dimensions (mm)	160 (W) x 428 (H) x 410 (D)	
Weight	10 kg (without HDDs for recording)	
Power Supply	built in 700W, with 230VAC input	
Power consumption/heatprint	250W/200W (without HDD for recording)	
Operating Temperature	5°C ~ 35°C	

Attention:

To support more than 1 RTSP stream and 1 ONVIF stream you will need special licence key.

