
NOVUS

NMS IP Recorder

NMS NVR X-4U-III





KEY FEATURES


















- •Supports resolution up to 4000 x 3000
- Recorded stream size: 450 Mb/s in total from all
- •Supports up to 3 monitors simultaneously
- •optional disk mounting: 8 x SATA 3,5"
- •External arrays support
- •Operating system: Microsoft Windows 10 IoT
- •Recording and surveillance system: NMS (Novus Management System)
- •Compatible with all NOVUS IP cameras

DIMENSIONS



RACK Mount 19"	4U

1//	П		n
VI	и	ב,	v

VIDEO	
IP Camera Recording	160 channels at 1920x1080 (video+audio) using H.264 codec • 200 channels at 1920x1080 (video+audio) using H.265 codec
Maximum Supported Camera Resolution	4000x3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Cameras and Protocols	Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye
Dualstreaming Support	yes
DISPLAY	
Monitor Output	1 x HDMI 2.0b, 1 x Dual link-DVI, 1 x Display Port 1.2 (up to 3 monitors simultaneously)
Maximum Resolution	3 x 4K UltraHD
AUDIO	
Audio Output	1 x HDMI, 1 x Display Port

PERFORMANCE - H.264

2MPX IP Camera	Recording up to: 160 main streams (while displaying: 8 sub streams) • Display up to: 60 sub streams or 20 main streams (while recording: 80 main streams) • Playback up to: 20 main streams (while recording: 80 main streams)
4MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 50 sub streams or 13 main streams (while recording: 80 main streams) • Playback up to: 13 main streams (while recording: 80 main streams)
5MPX IP Camera	Recording up to: 100 main streams (while displaying: 8 sub streams) • Display up to: 40 sub streams or 8 main streams (while recording: 80 main streams) • Playback up to: 8 main streams (while recording: 80 main streams)
8MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) • Display up to: 30 sub streams or 5 main streams (while recording: 60 main streams) • Playback up to: 5 main streams (while recording: 60 main streams)
12MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) • Display up to: 25 sub streams or 4 main streams (while recording: 50 main streams) • Playback up to: 4 main streams (while recording: 50 main streams)

PERFORMANCE - H.265

2MPX IP Camera	Recording up to: 200 main streams (while displaying: 8 sub streams) • Display up to: 60 sub streams or 20 main streams (while recording: 80 main streams) • Playback up to: 20 main streams (while recording: 80 main streams)
----------------	--







NMS IP Recorder NMS NVR X-4U-III

4MPX IP Camera	Recording up to: 160 main streams (while displaying: 8 sub streams) • Display up to: 40 sub streams or 9 main streams (while recording: 80 main streams) • Playback up to: 9 main streams (while recording: 80 main streams)
5MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) • Display up to: 35 sub streams or 4 main streams (while recording: 70 main streams) • Playback up to: 4 main streams (while recording: 70 main streams)
8MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) • Display up to: 25 sub streams or 4 main streams (while recording: 70 main streams) • Playback up to: 4 main streams (while recording: 70 main streams)
12MPX IP Camera	Recording up to: 90 main streams (while displaying: 8 sub streams) • Display up to: 16 sub streams or 4 main streams (while recording: 50 main streams) • Playback up to: 4 main streams (while recording: 50 main streams)
RECORDING	
Recording Mode	Continuous, Schedule, Panic, Triggered: manually, by alaram input, motion detection, video analysis, POS, temerature alarm
Schedule	individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes
Prealarm/Postalarm	Up to: 30s / Up to: 600s
PLAYBACK	
Recorded Data Search	By Date/Time, Events, "Text-in", Image Analysis Events
BACKUP	
Backup Methods	USB port (HDD lor Flash drive), Network
Backup File Format	JPEG, BMP, AVI, NMS
HDD	
Internal storage for system	1 x SSD NVMe
Internal Storage for Recording	
	8 available bays for 3,5" HDD surveillance grade storage media
ALARMS	8 available bays for 3,5" HDD surveillance grade storage media
ALARMS Alarm Input/output in cameras	8 available bays for 3,5" HDD surveillance grade storage media support of alarm input and output built in cameras
Alarm Input/output in cameras	support of alarm input and output built in cameras
Alarm Input/output in cameras Motion detection	support of alarm input and output built in cameras support of motion detection built in cameras
Alarm Input/output in cameras Motion detection Video Analytics	support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera
Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR)	support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras
Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm	support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras
Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK	support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera
Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface	support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client
Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface Network Throughput	support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP,
Alarm Input/output in cameras Motion detection Video Analytics Temperature alarm Licence plate recognition (LPR) NETWORK Network Interface Network Throughput Network Protocols Support	support of alarm input and output built in cameras support of motion detection built in cameras supported built in analytics in camera support of temperature alarm built in cameras support of selected image analysis functions available in the camera 2 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s up to 450Mbit/s from all cameras • up to 450Mbit/s to all client stations • Max network throughput: 450Mbit/s for each network card HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, SAMBA







NMS IP Recorder NMS NVR X-4U-III

ADDITIONAL INTERFACES

USB Ports	4 x USB 2.0, 4 x USB 3.2, 1 x USB 3.2 Type-C 2 x USB 2.0,
OPERATING SYSTEM	
Operating System	Microsoft Windows 10 IoT
Recording and Surveillance System	NMS (Novus Management System)
Additional Software	NMS, NOVUS MANAGEMENT SYSTEM AC, Internet Explorer
Operation Mode	Pentaplex
OSD	Polish, English, Russian, others
Control	PC mouse and keyboard (in-set included), DCZ keyboard
System Diagnostic	automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss
Security	Password protection, IP filtering, MAC filtering, Limiting the number of connections
INTEGRATION	
Integrated Devices	Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, NMS- ANPR Software, DSC Systems, POS Systems (Posnet, Upos and other), ONVIF Devices, RTSP Devices
INSTALLATION PARAMETERS	
Dimensions (mm)	178 (W) x 452 (H) x 648 (D)
Weight	28 kg (without HDD)
Power Supply	built in 700W, with 230VAC input
Power consumption/heatprint	350W/280W (without HDD for recording)
Operating Temperature	5°C ~ 35°C
RACK Mount 19"	4U

 $[\]ast$ To support more than two monitors it is required to use Display Port output.





^{**} Available with dual streaming mode.

^{***} Function capability depends on used devices and communication protocols.

^{****} List of compatible HDD models and maximum of their capacities is available in section DOWNLOADABLE FILES.