

### Speed Dome IP Camera with autonomous face recognition and intelligent object tracking

NVIP-4SD-6543/25/F





#### **KEY FEATURES**

















- •Resolution: 4 MPX
- •Lens: motorized varifocal, AI and AF function, optical zoom 25x, f=4.8  $\sim$  120 mm/F1.65  $\sim$  3.8
- •D/N function IR cut filter
- •Auto Tracking
- •Video content analysis based on Deep Learning
- microSD card support
- •WDR with double scan sensor
- •two-way audio
- •Min. Illumination from 0.002 lx (0 lx. IR on)
- •IR LED, range up to 160 m (depends on current optical zoom value)

#### **COMPATIBILITY**





#### **DIMENSIONS**

The camera is dedicated to work with NOVUS 6000 series recorders. Detailed data can be found in the compatibility table available in the DOWNLOADABLE FILES tab.

4 MPX CMOS sensor 1/2.7" SmartSens

#### **IMAGE**

Image Sensor

Number of Effective Pixels	2560 (H) x 1440 (V)
Min. Illumination	0.01 lx/F1.65 - color mode • 0.002 lx/F1.65 - B/W mode • 0 lx (IR on) - B/W mode
Electronic Shutter	auto/manual: 1/25 s ~ 1/30000 s
Wide Dynamic Range (WDR)	yes (double scan sensor), 120dB
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Reduction of image flicker (Antiflicker)	yes
LENS	
Optical Zoom	25x
Lens Type	motorized, auto-iris function, f=4.8 $\sim$ 120 mm/F1.65 $\sim$ F3.8
Auto-focus	zoom trigger, day/night mode trigger, manual trigger
DAY/NIGHT	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual, time
Switching Level Adjustment	yes
Switching Schedule	yes
Visible Light Sensor	yes
NETWORK	
Stream Resolution	2560 x 1440 (QHD), 2304 x 1296, 1920 x 1080 (Full HD), 1280 x 720 (HD), 704 x 576, 640 x 480 (VGA), 480 x 240, 352 x 288 (CIF)
Frame Rate	30 fps for each resolution
Multistreaming Mode	3 streams
Video/Audio Compression	H.264, H.264+, H.265, H.265+, MJPEG/G.711
Number of Simultaneous Connecti	onsmax. 10
Bandwidth	70 Mb/s in total



## NOVUS







## Speed Dome IP Camera with autonomous face recognition and intelligent object tracking NVIP-4SD-6543/25/F

Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, NTP,
, .	RTSP, RTP, UPnP, SNMP, QoS, IEEE 802.1X, PPPoE, SMTP, RTCP, ICMP, HTML5, RTMP
Camera Configuration	from Edge, Firefox, Chrome, Opera, Safari browser • languages: Polish, English, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS, NOVUS MANAGEMENT SYSTEM AC, N Control 6000
Mobile applications	N-VID6 (iPhone, Android)
PTZ	
Preset Commands	360 including 20 special (function) presets
Tours	8 (up to 16 presets per tour)
Patterns	4 (max. 360 commands or 180 s for each pattern)
Tilt/Pan Range	-3° ~ 90°/360° (continuous)
Pan/Tilt Speed	up to 200°/s (proportional to zoom)
Preset Speed	up to 240°/s
OTHER FUNCTIONS	
Privacy Zones	8 video mask type: single color
Motion Detection	yes
Video Content Analysis (VCA)	auto tracking linked to Video Content Analysis (VCA) functions, tamper, line cross, zone entrance, zone exit, cross counting, scene change, video blurred, video color cast, zone entrance detection and object tracking, objects distinguishing, comparing faces, intrusion detection
Image Processing	180° image rotation, sharpening, mirror effect
Prealarm/Postalarm	up to 6 s/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation, object tracking
Restoring default settings	via web browser, using reset button, via NMS IPTool software
IR LED	
LED Number	6
Range	up to 160 m (depends on current optical zoom value)
Smart IR	yes (hardware support)
INTERFACES	
Audio Input/Output	1 x  ack (3.5 mm)/1 x  ack (3.5 mm)
Alarm Input/Output	1 (NO/NC)/1 relay type
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 256GB
INSTALLATION PARAMETERS	
Dimensions (mm)	173 (Φ) x 268 (H) with bracket: 173 (W) x 415 (H) x 300 (L)
Weight	2.1 kg with bracket: 2.8 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	aluminium, white, IK10 impact rating, in set: outdoor housing (integrated with the camera), wall mount bracket
Power Supply	12 VDC, PoE+ (IEEE 802.3at, Class 4)
Surge protection	TVS 6000 V





# Speed Dome IP Camera with autonomous face recognition and intelligent object tracking NVIP-4SD-6543/25/F

Built-in Heater/Fan	yes/yes
Humidity	max. 90%, relative (non-condensing)
Cold start temperature	-30°C
Operating Temperature	-40°C ~ 60°C
Power Consumption	6 W • 15.5 W (IR illuminator on) • 22 W (IR and heater on)

The camera creates a fully functional face recognition system when used with selected NOVUS IP 6000 series recorders (models with "F" in the name). The above technical data and user manual apply to cameras supporting HTML5, available for sale from March 2024.

